



ALDO PRODUCTS COMPANY INC.

YOUR CUSTOM ADHESIVE & COATINGS SUPPLIER

1604 N. MAIN STREET
KANNAPOLIS, NC 28081
(704) 932-3054 / (800) 474-6019
(704) 932-3041 FAX
www.aldoproducts.com

ALDOCOAT 757 IGNITION BARRIER PROTECTIVE COATING FREQUENTLY ASKED QUESTIONS

1) What is an "ignition barrier"?

A protective covering or coating that will inhibit the igniting of flammable material and retard the spread of fire.

It is NOT a product that will 100% PREVENT the ignition of flammable materials.

2) What is the difference between an ignition barrier and a fire barrier?

An ignition barrier is required over polyurethane foam in non-living space environments (crawl space and attic areas).

A fire barrier is commonly understood as a product that meets the 15 minute code requirement.

3) What are the suggested spray equipment specifications?

A gas powered spray rig with a 5 hp engine, 3/8" hose up to 100 feet and a .031 reversible tip.

A Wagner electric paint sprayer will not be sufficient!

4) What is the suggested application method?

Airless sprayer, as described above, but the product can be rolled or brushed.

5) In what size containers of the product available?

Five gallon pails and fifty-five gallon drums. ALDO is also investigating alternative container sizes (i.e. three gallon pails)

6) Is the product considered hazardous material?

NO. ALDOCOAT 757 is a water-based coating that meets all EPA VOC standards and restrictions. As such, the product requires no special shipping or packaging requirements.

7) How do I clean up?

Soap and water only. No solvent is suggested to clean equipment; this may contaminate future product applications.

As with all applications, we suggest that equipment is cleaned after use, every day.

8) What is the shelf life of 757?

Six months is the standard shelf life is stored in ideal conditions (75°, 50% RH).

ALDO suggests that product be used as soon as possible after shipment to contractor/project site.

If stored at job site, we also suggest that product be kept out of direct sunlight.

9) What happens if the product freezes?

If ALDOCOAT 757 freezes, the integrity of the product may be compromised and unfir for use.

Signs of frozen product in pail may be coagulation of product (top layer) and/or cottage cheese type of consistency.

10) How do I dispose of product and/or empty pails?

Do not dispose of product in liquid form. Allow small quantities to cure before disposing.

Allow interior of pails to dry completely and dispose of in any dumpster.

11) How long after foam application do I have to wait before coating?

Once the foam is set up, just as in a roof application, the coating can be applied.

Avoid dust and debris from other surrounding construction to settle on foam.

12) What if I have product in my shop that it is beyond the shelf life?

Call ALDO Technical Department with four-digit lot number on the pail.

DO NOT proceed with using product that may be beyond its shelf life without prior approval to doing so!!

13) When is ALDOCOAT 757 available for shipment?

ALDO will have product available for shipment during the week of October 18, 2004.

Lead time may be required for drum orders.